

StreamLine

4816 StreamLine Smart LAR LTE-M Industrial



See indication of scale below

The 4816 StreamLine Smart LAR LTE-M Industrial is designed as a lightweight, long-term tracking solution, delivering exceptionally precise positional data. This module is suited tailored for tracking and tracing a wide range of items, including objects, livestock, and personal use. Equipped with BLE/RF connectivity and featuring a low-power GNSS receiver, alongside multiple on-board sensors and low-level I/O-connectivity, the 4816 StreamLine Smart LAR LTE-M Industrial is a versatile choice for your tracking needs.

Key features

General

- Small size 44 x 28 x 8mm
- 3 LEDs and 3 switches for user interaction
- Wide operating range: -40°C ... +85°C
- Multiple watchdog levels for maximum stability
- Event based free configurable module to fit any job with over 300 different events
- Define up to 4000 geozones
- Remote configurable to fit any job (both firmware and configuration files can be updated/patched over-the-air)
- Supports integration into third party networks
- User definable SMS commands

Optional extras

- Humidity sensor (sensitivity up to 2%RH)
- Barometer
- Altitude meter (sensitivity up to 10cm)
- Compass/3D Magnetometer
- eSIM

Connectivity

- LTE Cat M1, NB IoT cat NB2
- Integrated Bluetooth/RF 2,45GHz
- BLE range up to 60 m
- Proprietary RF range up to 300 m
- GNSS and mobile data antennas
- Nano SIM socket

Positioning

- GNSS

Sensors

- Temperature sensor (sensitivity up to 0,5°C)
- 3D accelerometer (sensitivity up to 16g)

Electrical

- Rechargeable 670 mAh battery
- +3 VDC output

Connectors

- Micro-USB connector

Interfacing

- Digital and Analog I/O
- iButton/1-Wire

StreamLine

Product summary

The 4816 StreamLine Smart LAR LTE-M Industrial boasts an array of customizable features, including programmable LED feedback, buttons, and a micro-USB port for charging and integrations.

This module acquires highly accurate positioning data through its dedicated GNSS receiver, enabling compatibility with GPS, A-GPS, Galileo, and Glonass. It effortlessly transmits its location via LTE-M/NB-IoT networks and seamlessly switches to 2G networks when needed. With multiple on-board sensors and versatile interaction options, coupled with the flexibility of freely configurable event-based settings and Digital and Analog I/O integration, it caters to a diverse range of custom IoT applications.

The module can be customised to specification when ordering in large volumes. Ask your StreamLine products supplier for more details.

Connectivity specifications

- Mobile data modem
 - Quectel BG95 M3 LTE cat M1, NB IoT cat NB2
 - All global certifications and R&TTE directives
 - Frequency bands: GSM/GPRS: 850/900/1800/1900 MHz
 - LTE: B1 ... 5, 8, 12, 13,18, 19, 20, 25 ... 28, 66, 85
 - BLE (2,45 GHz)
 - Nordic nRF51822
 - Protocol: Bluetooth Low Energy and custom 2,4 GHz protocol
 - Transmitting power: up to +20 dBm (with on-board amplifier)
 - Sensitivity: -93 dBm (BLE)
-

Navigation

- GNSS receiver
 - Quectel L76 GNSS (Glonass + GPS + Galileo) module
 - Frequency: GPS L1 1575,42 MHz C/A code, 48 search channels
 - Glonass L1 1598,0625 ... 1605,375 C/A code
 - Sensitivity: Acquisition -148 dBm (typical)
 - Reacquisition -160 dBm (typical)
 - Tracking -165 dBm (typical)
 - Position accuracy: <2,5 m CEP
-

Sensors

- Accelerometer
 - Sensitivity: light vibrations of 0,016 g up to movements of 16 g
 - Sensitivity can be adjusted over-the-air
 - Temperature sensor
 - Set alarm thresholds at specified temperatures
 - Accuracy up to 0,5 °C
-

StreamLine

Operating temperature

- With primary lithium cell
 - With rechargeable LiPo cell
- -40°C ... +85°C (discharging only)
 - -20°C ... +60°C (discharging)/ 0°C ... +45°C (charging)

Electrical


- Battery
 - Internal Lithium primary cell
 - Optional external +5 VDC with 10% variance (micro-USB-connector)
 - Charging current: 450 mA observing 0 ... +45 °C safety range for LiPolymer
 - Peak transmission current
 - Typical power consumption
- 2A
 - 20 mA, GPS tracking
 - 100 uA, modem and sensors power down, 4 inputs and 1 timer active

Battery connector



Pin	Description
• 1	• Temperature sensor
• 2	• Ground
• 3	• VCC, +3,4 ... +4,5 VDC battery connection

Micro-USB F



Pin	Description
• 1	• VCC, +4,5 ... +5,5 VDC charge input, max 600 mA
• 2	• Serial input or DI IN3 (+2 ... +31 VDC for active high) (Unless special action 72 is used then DI IN6) 50 k pulldown
• 3	• Serial or digital output 1, open collector (max +31 VDC/10 mA/100 mW)
• 4	• Analog input= %SG4 (0 ... +44 VDC)
• 5	• GND for charge and I/O

StreamLine

Optional on-board sensors

- Humidity sensor
- Sensitivity up to 2% RH
- Barometer/altitude meter
- Sensitivity up to 10 cm
- Compass
- 3D magnetometer for advanced position detection

Indication of scale



Size: 44 x 28 x 8 mm

About StreamLine IoT BV

StreamLine IoT BV is part of a group of companies active in the industry of track & trace modules, IoT solutions and internet portal services since 1995.

Disclaimer

StreamLine IoT BV reserves the right to make changes without further notice to any products herein to improve reliability, function or design. StreamLine does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.



©2024 StreamLine IoT BV
The Netherlands
www.streamline-iot.com
Version 2.1

Click [here](#) to view this product on our site.

