

StreamLine

4741 StreamLine LoRa CO2 Sensor



See indication of scale below

The 4741 StreamLine LoRa CO2 Sensor is designed for monitoring air quality, CO₂ levels and temperature. This module seamlessly integrates with facility management systems, enabling users to enhance indoor climate control while reducing expenses.

Key features

General

- Size: 86 x 86 x 26 mm
- Weight: 130 grams
- LED feedback
- Audible buzzer
- Wide operating range: -10 ° C ... +55 ° C (based on temperature sensor)
- Multiple watchdog levels for maximum stability
- Event based free configurable module to fit any job
- Remote configurable to fit any job (both firmware and configuration files can be updated/patched over-the-air)
- Supports integration into third party networks

Optional extras

- +5 VDC USB power supply

Connectivity

- Near Field Connection, get recent readings and update settings and firmware using an NDEF enabled phone
- LoRa technology, EU-868 MHz
- Compatible with the Helium network
- Bluetooth Low Energy for integrations in automation and feedback

Sensors

- Photoacoustic NDIR CO₂ sensor
- Temperature sensor up to 0,2 ° C accurate
- Humidity sensor
- 3D accelerometer up to 16 g

Electrical

- 3100 mAh battery capacity
- +3,7 VDC battery rating
- +5 VDC constant power

StreamLine

Product summary

The 4741 StreamLine LoRa CO2 Sensor is the ideal solution for managing air quality and climate in various indoor settings such as offices, schools, hospitals, and public buildings.

The module seamlessly integrates with facility management systems adjusting climate settings according to occupancy. This ensures a comfortable environment, factoring in variables like temperature, humidity, CO₂, and even optional VOC gas measurements.

The product boasts a highly accurate sensor utilizing photoacoustic NDIR technology, guaranteeing precision and an impressive sensor lifespan of 10 years without the need for interim calibrations. Moreover, measurements automatically adapt to humidity levels. Users can benefit from a definable multicolour LED for visual feedback on CO₂ levels, along with an audible warning for high CO₂ levels.

When ordered in large volumes, the device can be customised to specifications, e.g. adding or removing features. From only the PCBA up to a full solution (with enclosure, setting, special firmware, etc.), please contact your StreamLine products supplier for your project.

Connectivity specifications

- | | |
|-------------------|--|
| • LoRa | • Semtech SX 1261 <ul style="list-style-type: none">○ Frequency: EU 868 MHz○ Protocol: LoRaWAN 1.0.2 and custom LoRa protocol○ Transmitting power: +22 dBm○ Sensitivity: -148 dBm |
| • BLE (RF 2.4GHz) | • Nordic nRF52832 <ul style="list-style-type: none">○ Protocol: BLE 5.3 and custom 2,4 GHz○ Transmitting power: Up to +20 dBm with on board amplifier○ Sensitivity: -96 dBm (BLE) |
-

Sensors

- | | |
|--------------------------|--|
| • CO ₂ sensor | • Working range: 0 ... 5000 PPM |
| | • Sensor life: up to 10 years |
| | • See below for more details |
| • Humidity sensor | • Accuracy: 1,8% relative humidity |
| • Accelerometer | • Sensitivity: light vibrations of 0,016 g up to movements of 16 g |
| | • Sensitivity can be adjusted over-the-air |
-

StreamLine

Air quality sensor details

The air quality sensor is a photoacoustic NDIR sensor with a high level of accuracy in parts per million (PPM). The occupants of a room are affected by the levels of CO₂ ranging from a healthy work environment to discomfort to even adverse health effects. See below a table of the CO₂ levels in PPM and their effects on occupants.

-
- | | |
|----------------------|--|
| • 300 ... 450 PPM: | Typical variance for outdoor air (European Environment Agency, 2019) |
| • 500 ... 800 PPM: | Typical indoor air (European Committee for Standardization, 2019) |
| • 1000 ... 1200 PPM: | Recommended limit for indoor environments (European Committee for Standardization, 2019) |
-

Operating temperature

Temperature sensor range: -10 °C ... +55 °C

Battery operating range: -20 °C ... +60 °C

Electrical

Battery rated voltage +3,7 VDC

Nominal capacity 3100 mAh

Min. required current at +3,3 VDC 600 mA

Max. pulse current capacity 1000 mA

Optional extras

-
- | | |
|--------------------------|---|
| • 5 VDC USB power supply | • +5 VDC USB to molex cable (4143F) |
| | • Delivered with included fuse to protect the product from overcharge |
| | • Note: do not use different power cable |
-

StreamLine

Indication of scale



Size: 86 x 86 x 26 mm

About StreamLine IoT BV

StreamLine IoT BV is part of a group of companies active in the industry of track & trace devices, IoT solutions, and internet portal services since 1995.

Disclaimer

StreamLine IoT BV reserves the right to make changes to any products mentioned here to improve reliability, function, or design without prior notice. StreamLine does not assume any liability arising from the application or use of any product or circuit described here; nor does it convey any license under its patent rights or the rights of others. Any estimated calculations regarding power draw based on settings are meant only as an indication and do not reflect actual operational life.

LoRaWAN Certified^{CM} is a mark used under license from the LoRa Alliance[®].



The Netherlands

www.streamline-iot.com

Version 2.3

Click [here](#) to view this product on our site.



Sources

European Committee for Standardization. (2019). Energy performance of buildings - Ventilation for buildings. EN 16798-1:2019.

European Environment Agency. (2019). Trends in atmospheric concentrations of CO₂ (ppm), CH₄ (ppb) and N₂O (ppb), between 1800 and 2017. Retrieved from eea.europa.eu: [click here](#)